

# KIPP 2000

*The most powerful, versatile,  
user friendly pad printer*



## OPTIONAL

Pad cleaning attachment  
Dwell function valve for texture  
surface printing



Side way ink cup for long image  
printing (SCMIC)



Pneumatic shuttle attachment



Different size conveyor

## SPECIFICATIONS

Ink cup:	Ø 90 - 150 mm
Ink cup / Plate size:	100 x 250 mm - 180 x 350 mm
Ink tray / Plate size:	200 x 150 mm - 650 mm
Max. speed:	Up to 1,000 Cycles / Hr.
Max. pad pressure:	3,016N at 6 Bar
Power:	110/220V 50/60Hz 50W
Air consumption:	400 Litre / Min. (Approx.)
Size: L x W x H	1,090 x 710 x 1,750 mm
Weight:	280 Kg (Approx.)

## FEATURES

- Single color user-friendly automatic pad printer
- Pneumatic power operation
- Microprocessor with membrane switch control panel
- Heavy gauge steel construction machine frame
- Use Ceramic ink cup (CMIC) or open ink tray
- Use long life thin steel, polymer or 10 mm printing plate
- 0 - adjustment, Dead-on printing plate registration for fast job change
- Hardened, precision ground steel shaft with impregnated bushing ensures friction-free movement